

## **Soil Pipe Joiner Operating Instructions**

Cat. No. SPJ228 Item Code: #08070

Main Handle

## Orient Tool relative to pipe locations and prepare for use.

1. Orient the tool so:

A. The Hinged Jaw rests near the pipe end without the bell mouth.

B. The center housing jaw rests near the pipe end with the bell mouth.

- 2. Fully extend the screws on the chain.
- 3. Fully extend the Slide.

## Joining Soil Pipe

- 1. Bring pipes together as close as possible.
- With the tool oriented as described above, place the chain around the bell mouth of the first pipe. Next, place the chain into the slot on the Housing.
- 3. Turn Swivel Handle and tighten up the chain.
- 4. Place the chain from the Hinged Jaw around the other pipe and into the slot of the Hinged Hook.
- 5. Turn Swivel Handle and tighten up the chain.
- 6. Disengage the Yoke from the teeth on the Slide by pulling the Main Handle away from the pipe.
- 7. Pivoting off the Yoke Pins, move the Main Handle toward the bell mouth.
- 8. Engage the Yoke into the teeth by pushing the Main Handle toward the pipe.
- 9. Move the Main Handle away from the bell mouth. This action pulls the pipes together.
- 10. Repeat steps 6 through 9 until the pipe seats in the bell mouth.

Swivel Handle

Hinged Hook

Chain

Hinged Jaw

SPJ228 #08070

Reed Manufacturing Company 1425 West 8th St. Erie, PA 16502 USA



Phone: 800-666-3691 or 814-452-3691 Fax: 800-456-1697 or 814-455-1697